SUPER STRETCH / PCU AUTOMOTIVE FILM

Made in USA

TITANIUM CORE

A flexible, clear gloss film that follows sculpted panels and preserves the depth of the paint.



BRUSHED SILVER CARTON / GCC EDITION



NOMINAL THICKNESS

7.5 mil

ROLL FORMAT

1.52 m × 15 m

WRITTEN WARRANTY

10 years

EXCELERO

Installation & specification

Titanium Core / Super Stretch

Film construction

7.5 mil / 190 µm
NOMINAL INSTALLED GAUGE



Protective cap sheet Removable cover on the exposed face	**Removable**
Self-healing clear topcoat Controls surface finish and recovery	**10 µm**
Aliphatic PCU base film Flexible structural film body	**155 µm**
Optically clear adhesive Pressure-sensitive bond to paint	**25 µm**
Polyester release liner Removable backing on the adhesive	**≈75 µm**

Installed gauge excludes the cap and liner. Layer gauges are nominal. Diagram is schematic.

Film performance

	EDITION SPECIFICATION
Ultimate tensile strength	>15 MPa
Elongation at break	300%
Shrinkage after accelerated ageing	<0.1%
Initial 90° peel strength	>4 N/cm
Peel strength after 72 hours	>7 N/cm
Surface gloss	High

Elongation is a typical EXCELERO value. Tensile test method ASTM D638-95. Batches can vary.

Before you fit

01 Verify the box
Scan the QR on each carton before cutting. Save the roll serial with the job.

02 Check the finish
Under inspection lights, check clear gloss and the reflection across adjacent panels.

03 Confirm warranty terms
Ask the distributor for the written 10-year warranty and keep the purchase record.

WORLDWIDE ENQUIRIES

EXCELERO USA

Sales & professional support

sales@excelero.net

Find your regional team

excelero.net

Licensed patent US 8,765,263 B2 Full edition specifications Box verification

Manufactured by Saint-Gobain under licence from EXCELERO.

Finish reference photo by Jay Johnson / Pexels

SUPER MATTE / PCU AUTOMOTIVE FILM

Made in USA

STEALTH ROYAL

A clear matte film that softens reflections so the body lines and original colour stand out.



BLACK-AND-GOLD CARTON



NOMINAL THICKNESS	ROLL FORMAT	WRITTEN WARRANTY
7.5 mil	1.52 m × 15 m	10 years

EXCELERO

Installation & specification

Stealth Royal / Super Matte

Film construction

7.5 mil / 190 µm
NOMINAL INSTALLED GAUGE



Protective cap sheet	Removable cover on the exposed face	Removable
Self-healing matte topcoat	Controls surface finish and recovery	10 µm
Aliphatic PCU base film	Flexible structural film body	155 µm
Optically clear adhesive	Pressure-sensitive bond to paint	25 µm
Polyester release liner	Removable backing on the adhesive	≈75 µm

Installed gauge excludes the cap and liner. Layer gauges are nominal. Diagram is schematic.

Film performance

	EDITION SPECIFICATION
Ultimate tensile strength	>35 MPa
Elongation at break	500%
Shrinkage after accelerated ageing	<0.1%
Initial 90° peel strength	>4 N/cm
Peel strength after 72 hours	>7 N/cm
Surface gloss	Low

500% is the specification threshold. Tensile and elongation method ASTM D638-95. Batches can vary.

Before you fit

01 Verify the box
Scan the QR on each carton before cutting. Save the roll serial with the job.

02 Check the finish
Under broad light, check the matte sheen across adjoining panels before handing over the car.

03 Confirm warranty terms
Ask the distributor for the written 10-year warranty and keep the purchase record.

WORLDWIDE ENQUIRIES

EXCELERO USA

Sales & professional support

sales@excelero.net

Find your regional team

excelero.net

Licensed patent US 8,765,263 B2 Full edition specifications Box verification

Manufactured by Saint-Gobain under licence from EXCELERO.

Finish reference photo by Caleb Walley / Unsplash